



PRODUCT DATA SHEET

APOSTAR AR Single

Uninterruptible Power Supply 3kVA - 10kVA

Highlights

- AR Single 6 is available as rack mounting and free-standing tower
- swivelable display
- efficiency up to 92%
efficiency of 98% in "line – interactive" mode
- swappable batteries during operation



Nothing protects quite like Piller

PRODUCT DATA SHEET

APOSTAR AR Single



APOSTAR	AR Single 3	AR Single 6	AR Single 10
---------	-------------	-------------	--------------

Output

Rated power	3,3 kVA	6kVA	10kVA
Rated active power	2,3kW	4,2kW	8kW
Rated current	14A	26A	43A
Power factor	0,7 (ind.)	0,7 (ind.)	0,8 (ind.)
Rated voltage (adjustable)	220 / 230 / 240V	220 / 230 / 240V	220 / 230 / 240V
Frequency	50 / 60Hz	50 / 60Hz	50 / 60Hz

Input

Rated Voltage	164 - 276V	164 - 276V	138 - 276V
Frequency	45 - 65Hz	45 - 65Hz	45 - 65Hz
cos φ	0,98	>0,99	>0,98

General data

Width	175mm	175mm	2x 175mm
Depth	520mm	660mm	2x 660mm
Height	455mm	455mm	2x 455mm
Weight	38kg	64kg	1x 30 / 1x 65kg
Backup time	intern. 6min battery	intern. 8min battery	6min battery

UPS classification

VFI SS 111 according to IEC 62040-3

Interfaces (Standard)

- RS 232 / USB
- Potentialfree contact

Options

- external maintenance bypass for complete isolation of the UPS
- additional battery modules for extension of autonomy
- SNMP-adapter
- DATAWATCH (shut-down-software)
- remote monitoring- and failure analysis system for UPS units

www.piller.com

